



4' x 250'

ROOF UNDERLAYMENT

RUS4250PRO

Part No. 45389

Our synthetic roof underlayment is durable, tear-resistant, and can endure UV and moisture exposure. It's built to handle foot traffic during installation and remains effective even after rough handling!

FEATURES:

- ✓ Effectively repels moisture & resistant against mold growth
- ✓ Lightweight - 4X lighter than felt
- ✓ Fast installation
- ✓ Slip-resistant
- ✓ 180 day UV exposure
- ✓ 30 year limited warranty



Standards / Approvals:

ASTM D8257 • ASTM E 96-B • ASTM D4869 • ASTM D1204
ASTM D751-B • ASTM D5035 • ASTM D4533 • ASTM D228
ASTM D4798 • ASTM E108-A

**Get our
flyer digitally!**
Scan the QR code.



Product Details

Properties	Standard	RUS4250PRO
Unrolling	ASTM D8257	Pass
Pliability	ASTM D8257	Pass
Moisture Vapour Permeance	ASTM E96-B	Pass
Liquid Water Transmission	ASTM D4869	Pass
Linear Dimensional Change	ASTM D1204	MD 1.9% CD 1.8% Pass
Hydrostatic Resistance	ASTM D751-B	Pass
Tensile Strength (MD/CD)	ASTM D5035	MD 125lbs CD 80lbs Pass
Tear Strength (MD/CD)	ASTM D4533	MD 45lbs CD 40lbs Pass
Fastener Pull-through Resistance	ASTM D228	200 N Pass
Thermal Cycling	ASTM D8257	Pass
Laboratory Accelerated Weathering	ASTM D4798	Pass
Fire Resistance	ASTM E108-A	Pass

Material Description	RUS4250PRO
Thickness	7.5 Mil
Material Weight (per roll)	22 lbs
Temperature Range	-40°F - 240°F

To order, contact your local sales representative or please call 1-800-745-6735.

www.Interchange-Pro.com



4' x 250'

BASE PARA TECHO

RUS4250PRO

Parte: 45389

Nuestro base sintético para techo es duradero, resistente al desgarro y puede soportar la exposición a los rayos UV y a la humedad. Está diseñado para resistir el tránsito peatonal durante la instalación y mantiene su eficacia incluso después de un manejo rudo!

CARACTERÍSTICAS:

- ✓ Repele efectivamente la humedad y es resistente al crecimiento de moho
- ✓ Ligero - 4 veces más ligero que el fieltro
- ✓ Instalación rápida
- ✓ Resistente al deslizamiento
- ✓ Hasta 180 días de exposición a los rayos UV
- ✓ Garantía limitada de 30 años



Estándares / Aprobaciones:

ESR 5197 • ASTM D8257 • ASTM D226 • ASTM E108 Class A
Florida FBC#FL 42105 • AC188 • CAN/CSA A123.3

¡Obtén nuestro folleto digitalmente!
Escanea el código QR.



Detalles del producto

Propiedades	Estándar	RUS4250PRO
Desenrollado	ASTM D8257	Aprobado
Flexibilidad	ASTM D8257	Aprobado
Permeabilidad al vapor de humedad	ASTM E96-B	Aprobado
Transmisión de agua líquida	ASTM D4869	Aprobado
Cambio dimensional lineal	ASTM D1204	MD 1.9% CD 1.8% Aprobado
Resistencia hidrostática	ASTM D751-B	Aprobado
Resistencia a la tracción (MD/CD)	ASTM D5035	MD 125lbs CD 80lbs Aprobado
Resistencia al desgarro (MD/CD)	ASTM D4533	MD 45lbs CD 40lbs Aprobado
Resistencia al desprendimiento	ASTM D228	200 N Aprobado
Ciclos térmicos	ASTM D8257	Aprobado
Envejecimiento acelerado	ASTM D4798	Aprobado
Resistencia al fuego	ASTM E108-A	Aprobado
Descripción de Material		RUS4250PRO
Espesor		7.5 Mil
Peso de material (por rollo)		22 lbs
Rango de temperatura		-40°F - 240°F

Para pedidos, comuníquese con su representante de ventas local or llame al 1-800-745-6735.

www.Interchange-Pro.com