Pneumatic Tools

3 YEAR LIMITED WARRANTY

Get our flyer digitally!
Scan the QR code.

	NSC83-28 PRO	NSC90-34 PRO	NSR83-21 PRO	NSR83-21 PRO Framer	CRN4500 PRO
	Framing Nailer Part No. 65740	Framing Nailer Part No. 65745	Framing Nailer Part No. 65730	Framing Nailer Part No. 65735	Roofing Nailer Part No. 65750
Item Info					
Fastener Type	28° CLIPPED HEAD NAIL	30°-34° PAPER TAPE	21° ROUND HEAD NAIL	21° ROUND HEAD NAIL	RF ROOFING NAIL
Fastener Range	Length: 2" to 3-1/2" Shank Dia.: .113" to .131" Head Dia.: .275" to .283"	Length: 2" to 3-1/2" Shank Dia.: .113" to .131" Head Dia.: .275" to .283"	Length: 2" to 3-1/2" Shank Dia.: .113" to .131" Head Dia.: .275" to .283"	Length: 2" to 3-1/2" Shank Dia.: .113" to .131" Head Dia.: .275" to .283"	Length: 2" to 3-1/2" Shank Dia.: .113" to .131" Head Dia.: .275" to .283"
Magazine Capacity	86-94 Nails	86-94 Nails	64 Nails	64 Nails	86-94 Nails
Firing Mode	Selectable trigger - Bump or Sequential Fire	Bump or Sequential trigger options	Bump Fire	Bump Fire	Selectable trigger - Bump or Sequential Fire
Operating Pressure	70–120psi, 4.8–8.3 bar	70–120psi, 4.8–8.3 bar	70–120psi, 4.8–8.3 bar	70–120psi, 4.8–8.3 bar	70–120psi, 4.8–8.3 bar
Weight	8.4 lbs., 3.8 kgs.	8.4 lbs., 3.8 kgs.	8.2 lbs., 3.7 kgs.	8.2 lbs., 3.7 kgs.	8.4 lbs., 3.8 kgs.

3-Year Warranty on All Tools

	CN565-0 PRO	CN565-15 PRO	CN50-20 PRO	NSJH38-34 PRO	NSJH64-34 PRO
	Coil Nailer Part No. 65770	Siding Nailer Part No. 65765	Coil Nailer Part No. 65781	Joist Hanger Nailer Part No. 65755	Joist Hanger Nailer Part No. 65760
Item Info					
Fastener Type	0° COIL SIDING NAIL	15° COIL SIDING NAIL 15° COIL NAIL	20° PLASTIC COIL	MC METAL CONNECTOR NAIL	MC METAL CONNECTOR NAIL
Fastener Range	Length: 1-1/4" to 2-1/2" Shank Dia.: .080" to .105" Head Dia.: .216" to .236"	Length: Plastic: 1-1/4" to 2-1/2" Wire: 1-3/4" to 2-1/2" Shank Dia.: .083" to .099" Head Dia.: .197" to .236"	Length: 1-3/4" to 2" Shank Dia.: .086" to .092" Head Dia.: .197" to .224"	Length: 1-1/2" Shank Dia.: .131" / .148" Head Dia.: 0.28"	Length: 1-1/2" and 2-1/2" Shank Dia.: .131" / .148" / .162" Head Dia.: 0.28"
Magazine Capacity	300 Nails	200 Plastic Nails 250-400 Wire Nails	385 Nails	30 Nails	30 Nails
Firing Mode	Selectable trigger - Bump or Sequential Fire	Selectable trigger - Bump or Sequential Fire	Bump Fire	Sequential Fire	Sequential Fire
Operating Pressure	70–120psi, 4.8–8.3 bar	70–120psi, 4.8–8.3 bar	70–120psi, 4.8–8.3 bar	70–120psi, 4.8–8.3 bar	70–120psi, 4.8–8.3 bar
Weight	5.07 lbs., 2.3 kgs.	4.4 lbs., 2.0 kgs.	4.8 lbs., 2.2 kgs.	4.96 lbs., 2.25 kgs.	5.9 lbs., 2.7 kgs.

Pneumatic Tools

INTERCHANGE PRO®

3 YEAR LIMITED WARRANTY

Get our flyer digitally!
Scan the QR code.

	NEW!	NEW!	NEW!	NEW!	NEW!
	BN200 PRO Brad Nailer Part No. 65776	**SL150 PRO** Narrow Crown Stapler Part No. 65777	**FN250 PRO** Finish Nailer Part No. 65775	**DA250 PRO** Finish Nailer Part No. 65778	**MPN16 PRO** Finish Nailer Part No. 65779
Item Info					
Fastener Type	18 GA BRAD NAIL	18 GA NARROW CROWN STAPLE	16 GA STRAIGHT NAIL	15 GA ANGLED NAIL	
Fastener Range	Length: 5/8" to 2" Shank Dia.: 18 Gauge	Crown: 1/4" Leg Length: 3/8" to 1-1/2" Gauge: 18 Gauge	Length: 1-1/4" to 2-1/2" Shank Dia.: 16 Gauge	Length: 1-1/4" to 2-1/2" Shank Dia.: 15 Gauge	Length: 2" to 3-1/2" Shank Dia.: .08" to 0.162" Head Dia.: .344"
Magazine Capacity	110 Collated Brads	107 Staples	107 Collated Brads	107 Collated Nails	Single
Firing Mode	Selectable trigger - Bump or Sequential Fire	Selectable trigger - Bump or Sequential Fire	Selectable trigger - Bump or Sequential Fire	Selectable trigger - Bump or Sequential Fire	Single
Operating Pressure	70–120psi, 4.8–8.3 bar	70–120psi, 4.8–8.3 bar	70–120psi, 4.8–8.3 bar	70–120psi, 4.8–8.3 bar	70–120psi, 4.8–8.3 bar
Weight	2.7 lbs., 1.24 kgs.	2.6 lbs., 1.2 kgs.	3.8 lbs., 1.72 kgs.	4.6 lbs., 2.1 kgs.	1.1 lbs., 0.49 kgs.

3-Year Warranty on All Tools

	SP4016 PRO Wide Crown Stapler Part No. 65772	**SN5016 PRO** Medium Crown Stapler Part No. 65771	**SM125LN PRO** Medium Crown Stapler Part No. 65780	**SM150V PRO** "M" Wire Stapler Part No.	**HN500A** Coil Nailer Part No. 64281
Item Info					
Fastener Type	16 GA WIDE CROWN STAPLE	16 GA MEDIUM CROWN STAPLE	18 GA MEDIUM CROWN STAPLE		0° COIL SIDING NAIL
Fastener Range	Crown: 1" Leg Length: 5/8" to 1-1/2" Gauge: 16 Gauge	Crown: Medium 7/16" Leg Length: 1" to 2" Gauge: 16 Gauge	Crown: Medium 3/8" Leg Length: 5/8" to 1-1/4" Gauge: 18 Gauge	**NEW TOOL COMING SOON!**	Length: 3-1/2"to 5-1/8" Shank Dia.: .120" to 150" Head Dia.: .335" to .354"
Magazine Capacity	140 Staples	140 Staples	100 Staples		150 Nails
Firing Mode	Bump or Sequential trigger options	Selectable trigger - Bump or Sequential Fire	Trigger Fire (no safety)		Sequential Fire
Operating Pressure	70–120psi, 4.8–8.3 bar	70–120psi, 4.8–8.3 bar	70–120psi, 4.8–8.3 bar		70–120psi, 4.8–8.3 bar
Weight	5.29 lbs., 2.4 kgs.	4.3 lbs., 1.94 kgs.	2.97 lbs., 1.35 kgs.		13.42 lbs.,6.10 kgs.